

**WOODGRAIN'S SUPER STEP IS MANUFACTURED FROM 47# INDUSTRIAL PARTICLEBOARD. ENGINEERED FOR INTERIOR USE ONLY.**

**DESCRIPTION**

An engineered composite wood product cut into standard widths and lengths with one long edge rounded for ease of carpet installation.

**SPECIFICATION CONFORMANCE**

Physical and Mechanical Properties are averages from normal product runs.

**THICKNESS RANGE**

1 1/8" Only

**WOODGRAIN PARTICLEBOARD COMPLIES WITH:**

EPA TSCA Title VI, HUD 24 CFR 3280, CCR 93120 CARB ATCM Phase 2, CAN/CSA-0160-16 (Formaldehyde Emissions)  
 ECC CPA 4-11 (Sustainability); ANSI A208.1 2016 (Physical Properties)  
 Flame spread rating is class C (International Code Council – International Fire Code® and National Fire Protection Association 101 Life Safety Code®) as tested to ASTM E84 and CAN/ULC-S102-10.

<b>MANUFACTURING STANDARDS: AVERAGE</b>	<b>IMPERIAL</b>	<b>METRIC</b>
Density	47.0 lb/ft <sup>3</sup>	0.753 g/cm <sup>3</sup>
Internal Bond	115 psi	0.793 N/ mm <sup>2</sup>
Screw Hold - Face	310 lbs	1,379 N
Screw Hold - Edge	190 lbs	845.2 N
Formaldehyde, Emissions (TSCA Title VI)	< 0.09 ppm	< 0.09 ppm
Linear Expansion - Maximum	0.35%	0.35%
Water Absorption - Maximum	20%	20%
Moisture Content	7%	7%
Sanding	120 grit	-

<b>MANUFACTURING TOLERANCES</b>	<b>IMPERIAL</b>	<b>METRIC</b>
Thickness - Nominal	1 1/8 in	28.5 mm
Weight / MSF	4,433 lbs	2011 kg
Packaging - Pieces per Unit	56 pcs	-
Width - Standard (inquire if special width required)	11 1/4 in	-
Length - Standard (inquire if special length required)	8 ft, 10ft, 12ft	-

\*Target value 0.005 under nominal

For more information, including sales terms and conditions:

Visit our website: [Woodgrain.com](http://Woodgrain.com)

Send us an Email: [ParticleboardSales@Woodgrain.com](mailto:ParticleboardSales@Woodgrain.com)

Give us a Call: 888-264-7372

