

UNDERLAYMENT



DESCRIPTION

Woodgrain's Underlayment is acceptable for use in construction covered by HUD/FHA regulations and VA loans. The product meets the specifications of the American and Canadian national standards for flooring products (ANSI A 208.1.2016 Table B) and HUD Regulation 24 CFR Part 3280.

SPECIFICATION CONFORMANCE

Physical and Mechanical Properties are averages of all thicknesses from normal product runs. Engineered for interior use only.

THICKNESS RANGE

3/8", 1/2", 5/8", 3/4"

WOODGRAIN PARTICLEBOARD COMPLIES WITH:

EPA TSCA Title VI, HUD 24 CFR 3280, CCR 93120 CARB ATCM Phase 2, CAN/CSA-0160-16 (Formaldehyde Emissions)
ECC CPA 4-11 (Sustainability); ANSI A208.1 2016 (Physical Properties)
Flame spread rating is class C (International Code Council – International Fire Code® and National Fire Protection Association 101 Life Safety Code®) as tested to ASTM E84 and CAN/ULC-S102-10.

MANUFACTURING STANDARDS: AVERAGE	IMPERIAL	METRIC
Internal Bond	90 psi	0.621 N/ mm ²
Linear Expansion - Maximum	0.35%	0.35%

MANUFACTURING TOLERANCES	IMPERIAL	METRIC
Thickness Average from Target Value*	± 0.005 in	± 0.127 mm
Thickness Range (within panel) from Panel Average Value	± 0.004 in	± 0.1016 mm
Length and Width (within panel) from Specified Size	± 0.0625 in	± 1.5875 mm
Squareness (within panel) Maximum Deviation Between Diagonals	0.125 in	3.175 mm
Straightness (within panel) Maximum bow per 8' length	0.0625 in	1.5875 mm

*Target value 0.005 under nominal

For more information, including sales terms and conditions:

Visit our website: Woodgrain.com

Send us an Email: ParticleboardSales@Woodgrain.com

Give us a Call: 888-264-7372

